

drought tips

Number 92-24

Coping With Declining Groundwater Levels

In drought conditions, groundwater recharge is greatly reduced, eventually causing groundwater levels to decline. Declining groundwater levels, in turn, cause changes in pump performance, making longer irrigation times necessary to prevent deficit irrigation. Declining groundwater levels will also reduce the pressure of pressurized irrigation systems.

The following are measures for coping with declining groundwater levels:

1. Install a booster pump to increase the discharge pressure of the pumping plant. The pressure provided by the booster pump should equal the difference between the existing pressure and the normal operating pressure. A booster pump can also provide some suction lift in addition to the discharge pressure, which will increase the capacity of the pumping plant. The suction lift imposed on the booster pump should not exceed 20 to 25 feet.
2. If pumping levels decline to such an extent that suction no longer occurs in the intake pipe of the deep-well turbine, air will enter the pump and the capacity will decrease. This in turn will cause the water level in the well to rise. When the water level in the well rises, water

will again be pumped until the level is lowered and air enters the intake. This behavior causes surging, which can be corrected either by:

- a. lowering the pump, or
- b. reducing the drawdown (the difference between static water level and pumping water level) in the well by decreasing the pump discharge using one of the following options:

- Installing a throttle valve (butterfly or gate valve) in the pump discharge or reducing the number of laterals operating per set in a sprinkler or drip system.
- (For semi-open impellers only), raising the impeller.
- (For an engine-driven pump), decreasing the engine RPM.

3. Install a new pump capable of providing the desired discharge pressure and capacity at the greater pumping lifts. This will increase the horsepower demand and require a larger electric motor or engine.

4. Add an additional stage to the existing pumping plant. This will require a larger motor or engine.

Note: If surging in the well does not occur, lowering the pump will not increase the pump discharge. The pump discharge depends on the elevation dif-

ference between the discharge pipe and the pumping water level, not on the depth of the pump. Lowering the pump under these conditions may slightly decrease the discharge because of increased friction losses in the column pipe.

drought tips is a publication series developed as a cooperative effort by the following organizations:

California Department of Water Resource -Water Conservation Office
University of California (UC)
UC Department of Land, Air and Water Resources
USDA Drought Response Office
USDA Soil Conservation Service
USDI Bureau of Reclamation, Mid-Pacific Region

The University of California, in compliance with Titles VI and VII of the Civil Rights Act of 1964, Title IX of the Education Amendments of 1972, Sections 503 and 504 of the Rehabilitation Act of 1973, and the Age Discrimination Act of 1975, does not discriminate on the basis of race, religion, color, national origin, sex, mental or physical handicap, or age in any of its programs or activities, or with respect to any of its employment policies, practices, or procedures. Nor does the University of California discriminate on the basis of ancestry, sexual orientation, marital status, citizenship, medical condition (as defined in Section 12926 of the California Government Code) or because individuals are special disabled veterans or Vietnam era veterans (as defined by the Vietnam Era Veterans Readjustment Act of 1974 and Section 12940 of the California Government Code). Inquiries regarding this policy may be addressed to the Affirmative Action Director, University of California, Agriculture and Natural Resources, 300 Lakeside Drive, 6th Floor, Oakland, CA 94612-3560. (510) 987-0097.

Edited by Anne Jackson, UC Department of Land, Air and Water Resources
Published 1992